

INSTRUCTION

WARNING: BE CERTAIN THAT YOUR GUN IS UNLOADED AND POINTING IN A SAFE DIRECTION

COMPONENTS OF THE KIT

Triple Mount

Flashlight

Laser sight

- 1 Push button and 1 remote switch for flashlight
- 1 Push button and 1 remote switch for Laser sight
- 1 CR123A 3V. battery for flashlight
- 3 LR44 1.5V. batteries for Laser sight
- 2 Velcro stickers
- 3 "L" hex wrenches set

REPLACING THE FLASHLIGHT BATTERIES

Remove the light bulb assembly (located in the front end of the flashlight) by turning the cap counter-clockwise. Place the 3V battery (CR123A) inside, with the positive end facing out. Replace the light bulb assembly securely by turning it clockwise until tight. The flashlight is now ready for use.

EXCHANGING THE FLASHLIGHT SWITCHES

Remove switch assembly from the back of the flashlight by rotating counterclockwise until loose. Install the new switch by rotating it clockwise until tight and secure.

REPLACING THE LASER SIGHT BATTERIES

ATTENTION: THIS LASER TARGET DESIGNATOR IS A POWERFUL DEVICE THAT REQUIRES SPECIAL ATTENTION FOR ITS USE. READ THE FOLLOWING INSTRUCTIONS AND SAFETY PRECAUTIONS CAREFULLY BEFORE USE.

CAREFULLY BEFORE USE.

CAUTION: USE OF CONTROLS OR ADJUSTMENTS OR PERFORMANCE OF PROCEDURE OTHER THAN SPECIFIED HEREIN MAY RESULT IN HAZARDOUS RADIATION EXPOSURE.

AVOID DIRECT EYE EXPOSURE TO THE LASER BEAM. KEEP OUT OF THE REACH OF CHILDREN

Remove the switch assembly (located in the rear end of the flashlight) by turning it counter clockwise. Place the three LR44 1.5V batteries inside, with the positive end facing out. Replace the switch assembly securely by turning it clockwise until tight. The laser is now ready for use.

EXCHANGING THE LASER SIGHT SWITCHES

Remove the switch assembly from the back of the Laser sight by turning it counter-clockwise. Install the new switch by rotating it clockwise until tight and secure. The laser is now ready for use.

POSITIONING THE REMOTE SWITCHES

- Once you have decided the location of the switches on the rifle stock, place adhesive side of velcro strip on the stock of the rifle by pressing the adhesive portion against the stock.

- Attach the other adhesive portion to the back of the pressure sensitive switches by pressing the adhesive side of the surface of the Velcro strip against them.
- Secure the pressure sensitive switches to the stock by pressing both parts of the Velcro together.

WARNING: DO NOT LOOK DIRECTLY INTO THE LASER BEAM OUTPUT APERTURE DURING OPERATION. PERMANENT EYE DAMAGE MAY RESULT.

WARNING: EXERCISE SAFE GUN HANDLING. SHOOT ONLY AT AN APPROVED RANGE OR SUITABLE LOCATION. USE EYE AND EAR PROTECTION AS NECESSARY

ZEROING THE LASER

First, the laser needs to be aligned with the path of the pellet/bullet to do this follow the steps described below.

- 1) Activate the laser by pressing the switch.
- 2) From a bench rest position, fire three shots at the center of the target.
- 3) Observe where the pellets or bullets strike the target. Keeping the laser dot pointing at the center of the target and using the windage and elevation adjustments screws located in the laser body, move the laser dot to the center of the group formed by the three shots previously fired. Fire three more shots and note the points of impact on the target. Make additional adjustment of the Laser as necessary.

ADJUSTING THE LASER WINDAGE AND ELEVATION.

- The elevation adjustment screw is located on top of the laser. When the screw is turned counterclockwise, the Laser dot will move "Up" and when is turned clockwise the laser dot will move "Down".
- The windage adjustment screw is located at 45° angle on the right side of the laser body. When turned counterclockwise, the laser dot will move to the "Right". When turned clockwise the laser dot will move to the "Left"
- To align the laser dot with the center of the crosshairs of the reticle, move it by turning the windage and elevation screws on the Laser.

WARNING: DO NOT LOOK DIRECTLY INTO THE LASER BEAM OUTPUT APERTURE DURING OPERATION. PERMANENT EYE DAMAGE MAY RESULT.

WARNING: EXERCISE SAFE GUN HANDLING. SHOOT ONLY AT AN APPROVED RANGE OR SUITABLE LOCATION. USE EYE AND EAR PROTECTION AS NECESSARY